

SLBO-J-HT



SLBO-J-HT_TDS_V2_1/06/2017 *Allergene liste 07/12/2015

Chain oil for flaming machines/flame-off singers

The Frontmtec SLBO-J-HT is a food grade NSF-H1 registered, high-quality chain oil intended for application in the food and drink industry for temperatures from -30°C and up to +150°C.

The Frontmtec SLBO-J-HT is highly resistant to aging and free from resinification. The SLBO-J-HT can be used in locations in which there is a potential exposure of the lubricated part to food, and it offers a good protection against corrosion and is well compatible with plastics and sealings. SLBO-J-HT is compatible with mineral oils and is specifically designed for chains operating in flaming machines/flame-off singers, where it penetrates into the chains' inner surfaces.

At the same time, it is formulated to refrain from dripping down from the chains, and by use of sufficient amount of lubrication oil SLBO-J-HT, it can even prevent wear on the chains' outer surfaces, because of use of our unique high-temperature additive. Alternative recommended application is as a gearbox oil with long lifetime and a higher viscosity than SLBO-H-HT.

Specifications

| | |
|-----------------------|--|
| Chemical composition | Synthetic hydro-carbons registered according to NSF-H1, plus specially designed additives. All NSF-H1 registered. |
| NSF H1 Reg. number | 152257 |
| Density (25°C/77°F) | 0,85 g/cm ³ (+/- 0,01) |
| Appearance | Clear, bright |
| Operating temperature | -30°C to +150°C/-22°F to +302°F |
| Viscosity index | 175 |
| Refractive index | 1,460-1,470 |
| Package | 5 l/cans, 20 l/cans 1.32 gal/cans, 5.28 gal/cans |

Technical changes are subject to alterations!

Contact

Kolding, Denmark
E-mail: dkkol.aftersales@frontmtec.com
frontmtec.com